# **Product Information**

## **AVENO Mineral Super 30**

0002-000007



#### Description

AVENO Mineral Super 30 is a mineral mono-grade oil for petrol and diesel car engines with or without turbocharging and commercial vehicle engines. Facilitates extended oil change intervals as per manufacturer's instructions. With AVENO Mineral Super 30, a reliable and heavy-duty engine oil has been developed.

#### Instructions for use

AVENO Mineral Super 30 is an engine oil for year-round use, and is suitable for petrol and diesel car engines and commercial vehicle engines. AVENO Mineral Super 30 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification		
Specification		
API SF/CF	• MIL-L-2104 D	
• CCMC G4	• MIL-L-46152 B	
Recommendation		

• MB 227.0, MB 228.0

### **Properties**

- Suitable for catalytic converters
- A very good shear stability
- Prevention of black sludge formation
- A high oxidation stability

- A stable and excellent viscosity behavior
- Good detergent and dispersing properties
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming

Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	103	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	12,2	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	109		DIN ISO 2909:2004-08	
Appearance	YELLOWBROWN		VISUELL	
Density at 15°C	881	kg/m³	DIN EN ISO 12185:1997-11	
Pour Point	-33	°C	ASTM D 7346:2015	
Total Base Number (TBN)	7,3	mgkoh/g	ASTM D 2896:2015	