Product Information

AVENO Classic SAE 30 API SA

0002-000015



Description

AVENO Classic SAE 30 API SA is a year-round unalloyed engine oil whose composition has been specifically tailored to the needs of vintage vehicles without an oil filter. Suitable for petrol and diesel engines which have been developed for the mono-grade oils of their time. Due to its carefully selected base oils, AVENO Classic SAE 30 API SA is particularly resistant to oxidation, non-foaming and ensures fewer deposits and less wear because of its low ash content.

Instructions for use

AVENO Classic SAE 30 API SA is particularly recommended for pre-war engines which don't have oil filters and where sludge can settle in the oil sump. AVENO Classic SAE 30 API SA is also suitable for cars with vintage or old gearboxes.

Quality classification

Specification

• API SA

Properties

- Excellent material compatibility
- Selected base oils offer high protection against oxidation
- Prevents calcification and coking of cylinders, pistons and valves
- Secure lubricant film at high operating temperatures

Neutrality towards sealants

• Excellent protection against wear, corrosion and foaming

| Technical specifications | | | |
|------------------------------|--------|---------|--------------------------|
| Properties | Data | Unit | Testing under |
| Kinematic Viscosity at 40°C | 102,8 | mm²/s | DIN 51659-2:2017-02 |
| Kinematic Viscosity at 100°C | 11,4 | mm²/s | DIN 51659-2:2017-02 |
| Viscosity Index | 96 | | DIN ISO 2909:2004-08 |
| Appearance | YELLOW | | VISUELL |
| Density at 15°C | 880 | kg/m³ | DIN EN ISO 12185:1997-11 |
| Pour Point | -12 | °C | ASTM D 7346:2015 |
| Total Base Number (TBN) | 3,1 | mgkoh/g | ASTM D 2896:2015 |

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.