

Product Information

AVENO MotorCycle 4 Stroke Mineral 20W-50

0002-000126



Description

AVENO MotorCycle 4 Stroke Mineral 20W-50 is a mineral based engine oil with selected additives for demanding 4-stroke motorbikes. It is characterized by its high durability and reliability and is specifically designed for wet and lubricated couplings. AVENO MotorCycle 4 Stroke Mineral 20W-50 has an outstanding lubrication film adhesion and good shear stability as well as excellent cleaning properties and high resistance to aging.

Instructions for use

AVENO MotorCycle 4 Stroke Mineral 20W-50 is a suitable engine oil for all motorcycles, when the specification SAE 20W-50 JASO MA/MA2 is required. For professional racing we recommend our racing products.

Quality classification	
Specification	

- API SM
- JASO MA/MA2

Properties	
• Excellent cold starting properties	• High oxidation stability
• Excellent shear stability	• Very good detergent and dispersing properties
• Very good viscosity-temperature behavior	• Suitable for catalytic converters
• High safety margin even in boundary lubrication	• Prevents black sludge from forming

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	160,4	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	18,9	mm²/s	DIN 51659-2:2017-02
Viscosity Index	134		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -15°C	6700	mpa*s	ASTM D 5293:2020
Density at 15°C	879	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-33	°C	ASTM D 7346:2015
Total Base Number (TBN)	7,6	mgkoh/g	ASTM D 2896:2015