Product Information

AVENO MotorCycle 4 Stroke 10W-40

0002-000131



Description

AVENO MotorCycle 4 Stroke 10W-40 is a engine oil for demanding 4-stroke motorbikes. It allows for fuel-saving engine operation and is specifically designed for wet and lubricated couplings. AVENO MotorCycle 4 Stroke 10W-40 is characterized by its excellent cold starting properties, as it ensures optimum lubrication reliability during the cold-running phase.

Instructions for use

AVENO MotorCycle 4 Stroke 10W-40 is especially suitable as a high-performance, smooth-running engine oil for all motorcycles, when the specification JASO MA2 T904:2006 SAE 10W-40 is required. AVENO MotorCycle 4 Stroke 10W-40 meets the high-tech demands of the latest high-performance engine generation. For professional racing we recommend our racing products.

Quality classification					
Specification					
• API SL		• JASO MA2	• JASO MA2		
Recommendation					
• Aprilia		• Moto-Guzzi	• Moto-Guzzi		
• BMW		• Suzuki	• Suzuki		
• Ducati		• Triumph			
• Honda		• Yamaha	• Yamaha		
• Kawasaki					
Properties					
• Excellent cold starting properties		 Very stable viscosity 	Very stable viscosity index		
 Very good detergent and dispersing properties 		 Fast lubrication of t 	• Fast lubrication of the engine		
 Low evaporation, thus low oil consumption 		 No oil-related depo 	No oil-related deposits in combustion chambers, in piston ring zones and valves		
• Prevention of silting,	varnish, coking and corrosion				
Technical specification	S				
Properties	Data	Unit	Testing under		

Properties	Data	Unit	Testing under		
Kinematic Viscosity at 40°C	97,7	mm²/s	DIN 51659-2:2017-02		
Kinematic Viscosity at 100°C	14,4	mm²/s	DIN 51659-2:2017-02		
Viscosity Index	152		DIN ISO 2909:2004-08		
Appearance	YELLOWBROWN		VISUELL		
Viscosity CCS at -25°C	6400	mpa*s	ASTM D 5293:2020		
Density at 15°C	864	kg/m³	DIN EN ISO 12185:1997-11		
Pour Point	-36	°C	ASTM D 7346:2015		
Total Base Number (TBN)	7,7	mgkoh/g	ASTM D 2896:2015		

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.