Product Information

AVENO MotorCycle 4 Stroke 10W-60

855

-39

10,3

0002-000136



DIN EN ISO 12185:1997-11

ASTM D 7346:2015

ASTM D 2896:2015

Description

AVENO MotorCycle 4 Stroke 10W-60 is a heavy-duty engine oil for demanding 4-stroke motorbikes. It allows for fuel-saving engine operation and is specifically designed for wet and lubricated couplings. AVENO MotorCycle 4 Stroke 10W-60 is characterized by its excellent cold starting properties, as it ensures optimum lubrication reliability during the cold-running phase.

Instructions for use

Density at 15°C

Total Base Number (TBN)

Pour Point

AVENO MotorCycle 4 Stroke 10W-60 is especially suitable as a high-performance, smooth-running engine oil for all motorcycles, when the specification SAE 10W-60 is required. AVENO MotorCycle 4 Stroke 10W-60 meets the high-tech demands of the latest high-performance engine generation. For professional racing we recommend our racing products.

Quality classification				
Specification				
• API SL		• JASO MA/MA2	• JASO MA/MA2	
Properties				
• Excellent cold starting properties		 Very stable viscosity ir 	Very stable viscosity index	
 Very good detergent and dispersing properties 		 Fast lubrication of the 	• Fast lubrication of the engine	
• Low evaporation, thus low oil consumption		Prevention of oil-depe	Prevention of oil-dependent deposits in combustion chambers, in the piston ring area or	
• Prevention of silting, varnish, co	oking and corrosion	on valves		
Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	160,1	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	23,1	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	174		DIN ISO 2909:2004-08	
Appearance	YELLOWBROWN		VISUELL	
Viscosity CCS at -25°C	5900	mpa*s	ASTM D 5293:2020	

kg/m³

mgkoh/g

°C

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.