

# Product Information

## AVENO ATF DX VI RED

0002-000186



### Description

AVENO ATF DX VI RED is an automatic gear oil on a basis of the latest technology of HC/HT hydrocrack oils, which is permitted by General Motors for use in vehicles with automatic gearboxes. The special formulation ensures a lifespan that is twice as long as that of a comparable ATF oil. AVENO ATF DX VI RED meets the requirements of the gear oil specifications of General Motors for all vehicles with hydramatic automatic gearboxes from 2006 onwards.

### Instructions for use

AVENO ATF DX VI RED is fully backward compatible with DEXRON®-III (H), III and IIE applications. Always follow the recommendations in your vehicle's instruction manual.

### Quality classification

#### Specification

- GM Dexron® VI
- Aisin Warner AW-1

#### Recommendation

- ATF Type 3.0, ATF Type 3.1
- BMW/Mini ATF 3+
- Ford/Lincoln/Mercury XT-6-DSP [SP]
- Ford/Lincoln/Mercury XT-6-QSP [SP]
- Honda ATF DW-1
- Hyundai/Kia NWS 9638 T-5
- Jaguar/Land Rover Fluid 8432
- Mazda FZ, Mazda FW 6A EL, Mazda FW 6AX EL
- MB 236.12, MB 236.14, MB 236.41
- VOLVO 97342 (AT 102)
- Mitsubishi ATF-J3, Mitsubishi Diaqueen ATF-PA
- Nissan Matic-S
- Porsche 000 043 304 00
- Shell 3353/134/M-1375.4/12108
- SP-IV/SPH-IV/SP-IV-RR
- Toyota Scion FZ, Toyota WS (JWS 3324)
- Volvo 97342 AT102
- VW G 052 533, VW G 055 005 A/A2
- VW G 055 540 A2, VW G 060 162 A1/A2/A6
- ZF Lifeguardfluid 5/6

### Properties

- Superior wear protection
- Longer change intervals
- Excellent fluidity at low temperatures
- Good resistance against lubricant failures under hard operating conditions
- Outstanding resistance to oil sludge and deposit formation
- Prevention of coupling grinding in modulation rotary converters

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	29,7	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	6,0	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	154		DIN ISO 2909:2004-08
Appearance	RED		VISUELL
Density at 15°C	841	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-51	°C	ASTM D 7346:2015