

Product Information

AVENO Premium LL-12 FE 0W-30

0002-000500



Description

AVENO Premium LL-12 FE 0W-30 is a synthetic mid SAPS oil for petrol and diesel engines with and without turbocharging. AVENO Premium LL-12 FE 0W-30 offers significant fuel economy through its formulation, protecting the turbocharger from sedimentation for maximum performance.

Instructions for use

AVENO Premium LL-12 FE 0W-30 is a fuel-efficient oil and suitable for year-round use, especially for new BMW gasoline and diesel engines. AVENO Premium LL-12 FE 0W-30 is suitable for extended oil change intervals. The operating regulations of the motor vehicle and engine manufacturers are to be observed.

Quality classification			
Specification			
<ul style="list-style-type: none">• ACEA A5/B5• ACEA C2		<ul style="list-style-type: none">• API SP (RC)• ILSAC GF-6	
Recommendation			
<ul style="list-style-type: none">• BMW Longlife-12 FE• MB 227.61, 229.61		<ul style="list-style-type: none">• Ford WSS-M2C950-A	
Properties			
<ul style="list-style-type: none">• Excellent cleaning and dispersing properties• Excellent protection against wear, corrosion and foaming• Very good cold start properties		<ul style="list-style-type: none">• Constant oil layer density at different temperature and pressure controls• Excellent fuel economy under all operating conditions	
Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	48,5	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	9,8	mm²/s	DIN 51659-2:2017-02
Viscosity Index	194		DIN ISO 2909:2004-08
Appearance	YELLOW BROWN		VISUELL
Density at 15°C	846	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015